


TWO DAYS TRAINING ON THE OPERATION AND MANAGEMENT OF WWTPS

9-10 September, Murcia

Conventional and advanced tertiary treatment

Presented by: Pedro Simon Andreu






Aerobic treatment



Anaerobic treatment





Conventional activated sludge




Extended aeration



Double - stage





Sequencial Batch Reactor






Membrane Biological Reactor (MBR)

















Trickling-Filter







Rotating Biological Contactors







7

Biological Treatment Processes	Facilities
Conventional Activated Sludge	6
Extended Aeration	70
Double Stage	3
MBR	7
Lagooning	1
RBC	1

Number of Murcia Region wastewater treatment facilities by Biological Process

WWTP Range	Facilities number	Treated volume (m³/year)	%
≤ 500 p.e.	22	377.846	0,35
500 - 2.00 <mark>0</mark> p.e.	22	1.354.592	1,24
2.000 - 20.000 p.e.	22	19.038.591	17,4
20.000 - 100.000 p.e.	19	34.387.240	31,43
≥100.000 p.e.	3	54.248.405	49,58
TOTAL	88	109.406.674	100

Construction Cost

WWTP	Construction cost (€)	Building year	Capacity (m3/day)	Treatment
Abanilla	1.178.638	2001	1500	E.A.+Ph-Ch+SF+UV
Barinas	1.201.615	2008	540	E.A.+RF
Alhama	3.376.069	2003	5400	E.A.+SF+UV
Beniel	4.646.400	2005	5000	E.A.+Ph-Ch+SF+UV
Caravaca	6.552.557	2005	8000	E.A.+Ph-Ch+SF+UV
Ceuti	5.605.258	2007	8000	E.A.+Ph-Ch+RF+UV
Jumilla	7.721.835	2007	12000	E.A.+Ph-Ch+SF+UV
Lorquí	4.719.755	2006	5000	E.A.+Ph-Ch+SF+UV
Mazarrón	6.618.273	2004	15000	E.A.+Ph-Ch+RF+UV
Moratalla	4.411.500	2005	4500	E.A.+Ph-Ch+SF+UV
Mula	5.164.800	2007	6000	E.A.+Ph-Ch+DF+UV
San Javier	17.541.300	2007	22500	E.A.+Ph-Ch+SF+UV
Torrepacheco	4.006.572	2004	5000	E.A.+Ph-Ch+SF+UV
Torres de Cotillas	7.963.328	2007	12000	E.A.+Ph-Ch+SF+UV
Los Alcázares	15.415.765	2008	22500	E.A.+Ph-Ch+SF+UV
San Pedro	13.410.000	2007	20000	MBR
Cabezo Beaza	15.276.314	2001	35000	CAS
Murcia Este	40.992.300	2000	100000	CAS (A2O modified)

Where:

CAS: Conventional Activated Sludge


E.A.: Extended Aeration

Ph-Ch:Physical-Chemical Process

SF: Sand Filter

RF: Ring Filter DF: Disc Filter

Level of treatment	Number of facilities	Treated Volume (Hm³/year)	%
Tertiary Treatment	53	49,98	45,68%
Secondary Treatment	34	57,953	52,97%
Lagooning	1 1,511		1,38%
	88	109,407	100%



Segura River mouth

Unit process for complying with Reuse Legislation


- Suspended Solids
- > Turbidity
- Escherichia Coli
- Helminth eggs

Filtration

Physical-Chemical process and filtration

Filtration + Disinfection

Filtration





Flow equalitation tank






Algae Problem








Physical-Chemical Process (coagulation and flocculation)



Lamella tube settler



Size of helminth eggs



Sand Filter



Continuous Cleaning sand filter



Cloth Filter









Membrane Disc Filter



Ring-Filter















Sand Filter



Sand Filter Problems









Sand Filter Problems







Leopold System









- Cloth Filter
- Closed Sand Filter
- Open Sand Filter

- Ring Filter
- Disc Filter
- Continuos Cleaning Sand Filter









Disinfection systems







Open channel







Closed channel












UV dose requirements include effects of photoreactivation

Source: University of Bonn


Effective dossage for different organisms












Transmittance



Average, maximum and minimum transmittance for Murcia Region WWTP

	IRANSMITANCIA			
	PROMEDIO	MÁXIMO	MÍNIMO	
EDAR	(%)	(%)	(%)	
Molina Norte	45,1	53,4	31,4	
San Pedro	73,0	78,0	69,0	
Mazarrón Nueva	67,0	73,0	51,0	
Torres de Cotillas	54,8	58,9	51,3	
Caravaca de la Cruz	63,0	69,0	58,0	
Alhama	57,0	61,0 70,0 54,7	42,0 51,0 33,1	
Torrepacheco	61,0			
Mula	41,9			
Santomera Norte	45,6	50,9	43,3	
Lorquí nueva	55,0	60,0	46,2	
Jumilla Nueva	59,9	62,0	52,2	
Ceutí Nueva	50,0	60,0	30,0	
Beniel nueva	60,2	65,1	54,7	
Roldán, Lo Ferro y Balsicas	60,0	66,0	50,0	
Fuente Álamo	62,0	66,0	55,0	
Abanilla	55,6	57,5	53,4	
Calasparra MBR	52,8	57,9	48,0	
Moratalla	55,0	67,0	42,0	
Librilla	59,0	67,0	53,0	
MEDIA	56,7	63,0	48,1	
mínimo	41,9	50,9	30,0	
má×imo	73,0	78,0	69,0	

TRANSMITANCIA

WWTP	Design Flowrate (m3/h)	Design transmittance (%)	Disinfection required	Number of lamps	Real Flowrate (m3/day)	Flow equalition tank	Real transmittance (%)
1	333	65	2,2 TC	80	8.000	Not	55
2	500	65	2,2 TC	120	5.000	Not	59,9
3	600	65	10 FC	64	6.000	Not	46,2
4	208	65	2,2 TC	48	5.000	Not	62
5	1042	65	5 CF	192	25.000	Yes	51,2

Real facilities

UV: Aspects to consider


Design:

- Real higher flowrates
- Automatic cleaning system
- Real lower transmittance
- No residual effect

Operation:


- Energy intensive
- Difficult dose control when changing lamps
- Non-original lamps





Item	Average cost (€)	%
Personnel	0,013	20,74
Maintenance	0,013	20,96
Lamps reposicion	0,011	18,47
Reagents	0,002	3,35
Drinkable water	0,00013	0,22
Energy	0,021	33,87
Sludge	0,002	3,07
TOTAL COST	0,06213	,

Treatment tertiary: Ph-Ch + Llam-Set + Sand Filter + UV



Working in other disinfection systems

مع خالص شكري وامتناني

Thank you for your attention

Merci pour votre attention



For additional information please contact:

Sustainable Water Integrated Management – Support Mechanism: <u>info@swim-sm.eu</u> Website: <u>www.swim-sm.eu</u>